

Index

A

Alarm Mode Read: R#, ,
Alarm Mode Write: W#, ,
Alarm Temperature Read: R%, ,
Alarm Temperature Write: W%, ,
AP, ,
AS, ,
Auto-tuning Bit,
Auto-tuning Start: AS, ,
Auto-tuning Stop: AP, ,

B—C

block format,
character check,
Cold Junction Compensation Error,
command block,
commands
 according to application,
 list,
 control operation start and stop,
 list,
 fuzzy control,
 list,
 heater burnout and SSR failure detection,
 list,
 heating and cooling control,
 list,
 list,
 temperature control,
 list,
Communication Test: TS, ,
communications
 errors,
 procedure,
Control Mode Bit,
control output, read, percentage,
Control Period Read: RT, ,
Control Period Write: WT, ,
Cooling Coefficient Read: RC, ,
Cooling Coefficient Write: WC, ,
CPU Error,
Current Transformer Input AD Error,

D

Dead Band and Overlap Band Read: RD, ,
Dead Band and Overlap Band Write: WD, ,
Derivative Time Read: RV, ,
Derivative Time Write: WV, ,

E

end codes
 list,
 priority,
error
 cold junction compensation,
 CPU,
 current transformer input AD,
 detection,
 memory,
 processing,
 sensor input AD,
 setting data,
error codes, list,
Error Read: RU, ,
errors, undefined,

F

FCS, ,
 calculations,
format check,
Frame Check Sequence. *See* FCS
framing check,
Fuzzy Scale 1 Read: Rk, ,
Fuzzy Scale 1 Write: Wk, ,
Fuzzy Scale 2 Read: Rl, ,
Fuzzy Scale 2 Write: Wl, ,
Fuzzy Strength Read: Rj, ,
Fuzzy Strength Write: Wj, ,

H

HB Alarm and HS Alarm Point Read: RU, ,
HB Alarm and HS Alarm Point Write: WU, ,
header code,
Heater Burnout and SSR Failure Detection Current Value Read:
 RW, ,
Heater Burnout and SSR Failure Detection Current Value
 Write: WW, ,

Heater Current Overflow Bit,

Heater Current Value and SSR Leakage Current Value Read:
RZ, ,

Hysteresis Read: RH, ,

Hysteresis Write: WH, ,

I

Initialize Setting Data: MC, ,

Input Shift Read: RI, ,

Input Shift Write: WI, ,

Integral Time Read: RN, ,

Integral Time Write: WN, ,

M

manipulated variable, read, percentage,

Manual Operation Start: OM, ,

Manual Output Value Write: WO, ,

Manual Reset Value Read: RK, ,

Manual Reset Value Write: WK, ,

MC, ,

Measured Temperature Read: RX, ,

Memory Bank Designation Read: RM, ,

Memory Bank Designation Write: WM, ,

Memory Error,

Memory Write Bit,

Memory Write: WE, ,

N—O

numeric value check,

OM, ,

OP, ,

Operation Start: OS, ,

Operation Stop: OP, ,

OS, ,

Output Operation (Normal/Reverse) Read: RU, ,

Output Operation (Normal/Reverse) Write: WU, ,

Output Operation Bit,

Output Value Read: RO, ,

Output Variable Change Rate Limit Value Read: RG, ,

Output Variable Change Rate Limit Value Write: WG, ,

Output Variable Limit Value Read: RL, ,

Output Variable Limit Value Write: WL, ,

overrun check,

P

Present Set Point Read: Rs, ,
process value, read,

Process Value Overflow Bit,

Process Value Underflow Bit,

Proportional Band Read: RB, ,

Proportional Band Write: WB, ,

R

R#, ,

R%, ,

Ramp Value Read: RR, ,

Ramp Value Write: WR, ,

RB, ,

RC, ,

RD, ,

reading data,

reception buffer,

response block,

RG, ,

RH, ,

RI, ,

Rj, ,

RK, ,

Rk, ,

RL, ,

RI, ,

RM, ,

RN, ,

RO, ,

RR, ,

RS, ,

Rs, ,

RT, ,

Rt, ,

RU, , , , , ,

RUN Status Bit,

RV, ,

RW, ,

RX, , , ,

RZ, ,

S

Sensor Input AD Error,
Sensor Input Error Bit,
Set Point Read: RS, ,
Set Point Write: WS, ,
Setting Data Error,
setting unit, temperature
 read, ,
 write, ,
Setting Unit Read: Rt, ,
Setting Unit Write: Wt, ,
start character,
Status Read: RX, ,

T–V

terminator,
text,
TS, ,
unit number,
vertical parity check,

W

W#, ,
W%, ,
WB, ,
WC, ,
WD, ,
WE, ,
WG, ,
WH, ,
WI, ,
Wj, ,
WK, ,
Wk, ,
WL, ,
Wl, ,
WM, ,
WN, ,
WO, ,
WR, ,
writing data,
WS, ,
WT, ,
Wt, ,
WU, , , ,
WV, ,
WW, ,